

- from calcium build-up and premature failure
- For use with traditional water heaters and tankless water heaters
- Installation is approved for Copper, PEX, CPVC and SCH40/80 PVC - Installation is bi-directional flow
- Point-of-Entry protection
- Water quality reporting via app

Product Code	BTCW2234
Body Connection	ı" MPT
Optimum Working Flow Rate	15 GPM
Maximum Operational Flow	25.4 GPM
Length/Width	23.5"x 12"
Warranty*	5 years

## WHY CLEAN WHEN YOU CAN PREVENT—HOW DOES THE LIME DEFEAT WORK?

Water enters the Lime Defeat and is immediately directed by the revolutionary turbulent amplifier which sends the water into a spinning motion to help ensure maximum efficiency of the water being processed.


The water is then sent through a series of Zinc anodic channels, which when combined with Lime Defeat natural electrolytic process helps change the calcite mineral to the smooth, non-adhering Aragonite.



This Aragonite crystal has a smooth external surface which prevents it from adhering to domestic pipework, boilers and appliances. It remains in suspension until it is then passed down the drain.



If at any point these particles made their way onto a surface, they become much easier to remove without any need for cleaning agents or aggressive cleaning action.



BONDURANT TECHNOLOGIES INTERNATIONAL INC. 233 SMITHSTONE PATH, FAYETTEVILLE GA 30214 WWW.BONDURANTTECHNOLOGIES.COM

**CONTACT:**